

**IN THE CLAIMS:**

**A. Please cancel claim 3 without prejudice or disclaimer.**

**B. Please amend claims 1 and 2 as follows:**

**Amended Claims With Mark-ups to Show Changes Made**

1. (Amended) An electron gun in a [color] cathode ray tube (CRT) comprising:  
a plurality of stem pins for applying different voltages;  
an acceleration electrode, a third electrode, a fourth electrode, and a static electrode[,] for forming pre-focus lenses;  
a dynamic electrode and an anode for forming a main focus lens, the dynamic and static electrodes forming a quadrupole lens;  
[the static electrode and the dynamic electrode for forming a quadrupole lens;]  
a bead glass for holding the foregoing electrodes at fixed distances; and [,]  
a wire having one end welded to the third electrode, the other end welded to a  
[the] stem pin applying a dynamic voltage [applied thereto], and a body of the wire between the  
one end and the other end of the wire [having an evasive form so as not to come into contact  
with neighboring members], wherein the body of the wire is arranged so as not to pass through  
a space formed between an outer surface of the bead glass and an inner surface of a neck tube  
of the cathode ray tube.

2. (Amended) An electron gun in a [color] cathode ray tube (CRT) comprising:

- a plurality of stem pins for applying different voltages;
- an acceleration electrode, a third electrode, a fourth electrode, and a static electrode[,] for forming pre-focus lenses;
- a dynamic electrode and an anode for forming a main focus lens, the dynamic and static electrodes forming a quadrupole lens;
- [the static electrode and the dynamic electrode for forming a quadrupole lens;]
- first and second bead glasses [glass] for holding the foregoing electrodes at fixed distances;
- a first wire having one end welded to the dynamic electrode, the other end welded to a first [the] stem pin for applying a dynamic voltage [applied thereto], and a first body of the first wire between the one end and the other end [having an evasive form so as not to come into contact with neighboring members]; and [,]
- a second wire having one end welded to the third electrode, the other end welded to a second [the] stem pin for applying a static voltage [applied thereto], and a second body of the second wire between the one end and the other end [having an evasive form so as not to come into contact with neighboring members], wherein the first and second wires are arranged so as not to pass through a space formed between an outer surface of each of the bead glasses and an inner surface of a neck tube of the cathode ray tube.